

# HARTON

## vented units

### plumbing system 1

**Suitable for the flat with electric supply only.**

**Standard Plumbing unit with direct hot water cylinder and cold water storage.**

**This unit includes the following:**

- Welded steel frame assembly.
- Sealed cold water storage tank, including ball valve and overflow connection.
- Insulated hot water cylinder with two immersion heater bosses capped.

Interconnecting pipe work and isolation valves between the storage tank and cylinder including a cold down service.

This unit requires (by others) two 3Kw power supplies to the immersion heaters, with an incoming water main, overflow, and domestic hot and cold water service connection.

As an optional extra Harton can offer fitted immersion heaters and immersion heater timer/boost controls.

**The Harton direct standard units come in the following sizes:**

Order code	227 ltr. cold water
10/23/120	610 x 610 x 2050 high
11/23/144	610 x 610 x 2050 high
12/23/166	610 x 610 x 2200 high
13/23/210	650 x 650 x 2050 high
Order code	180 ltr. cold water
14/34/120	610 x 610 x 1900 high
15/34/144	610 x 610 x 1900 high
16/34/166	610 x 610 x 2050 high
17/34/210	650 x 650 x 1900 high

*Note, the third number of the order code indicates the hot water capacity in ltrs.*

Harton can of course offer variations to the above if required.

All our potable water materials are WRAS approved.



*Harton have been designing and building Prefabricated Plumbing Units for over 50 years. Our products offer the attraction of guaranteed consistency in the high quality of material, method of installation and easy maintenance.*

Harton, Unit 6 Thistlebrook Industrial Estate, Eynsham Drive, London SE2 9RB

**Tel: 020 8310 0421 Fax: 020 8310 6785 Email: [info@hartons.co.uk](mailto:info@hartons.co.uk)**