

HARTON

vented units

plumbing system 2

Suitable for open vented heating system.
Standard Plumbing unit with indirect hot water cylinder, cold water storage and expansion tank.

This unit includes the following:

- Welded steel frame assembly.
- Sealed cold water storage tank with integral heating expansion tank, including ball valves and overflow connections.
- Insulated hot water cylinder with one immersion heater boss capped.
- Interconnecting pipe work and isolation valves between the storage tank and cylinder, including a cold down service.

This unit requires (by others), a 3Kw power supply to the immersion heater, an incoming water main, overflow connection, domestic hot and cold water services connections, and primary connections.

As an optional extra Harton can offer a fitted immersion heater with or without timer controls.

The Harton indirect standard units come in the following sizes:

Order code	204/20 ltr. cold water
48/35/114	610 x 610 x 2050 high
49/35/140	610 x 610 x 2050 high
50/35/162	610 x 610 x 2200 high
51/35/200	650 x 650 x 2050 high

Note, the third number of the order code indicates the hot water capacity in ltrs.

Harton can of course offer variations to the above if required.

All our potable water materials are WRAS approved.



Harton have been designing and building Prefabricated Plumbing Units for over 50 years. Our products offer the attraction of guaranteed consistency in the high quality of material, method of installation and easy maintenance.

Harton, Unit 6 Thistlebrook Industrial Estate, Eynsham Drive, London SE2 9RB

Tel: 020 8310 0421 Fax: 020 8310 6785 Email: info@hartons.co.uk