

HARTON

vented units

plumbing system 4

Suitable for a flat with electric supply only.
Standard Plumbing unit with direct hot water cylinder and boosted hot and cold water services.

This unit contains the following:

- Sealed cold water storage tank, including ball valve and overflow connection.
- Insulated hot water cylinder with two immersion heater bosses capped.
- Integrated twin 1.5 bar negative head pump boosting the hot and cold water services (larger duty pumps available).
- Interconnecting pipe work and isolation valves between the storage tank and cylinder including a cold down service.

This unit requires (by others), a 5amp spur, to the domestic booster pump, and two 3Kw power supplies to the immersion heaters, an incoming water main, overflow connection, and domestic hot and cold water services connections.

As an optional extra Harton can offer fitted immersion heaters and immersion heater timer/boost controls.

The Harton direct standard units come in the following sizes:

Order code	227 ltr. cold water
18/23/120/B	610 x 700 x 2050 high
19/23/144/B	610 x 700 x 2050 high
20/23/166/B	610 x 700 x 2200 high
21/23/210/B	650 x 750 x 2050 high
Order code	180 ltr. cold water
26/34/120/B	610 x 700 x 1900 high
27/34/144/B	610 x 700 x 1900 high
28/34/166/B	610 x 700 x 2050 high
29/34/210/B	650 x 750 x 1900 high

Note, the third number of the order code indicates the hot water capacity in ltrs.

Harton can of course offer variations to the above if required, access to the unit can be front or end on.

All our potable water materials are WRAS approved.



Harton have been designing and building Prefabricated Plumbing Units for over 50 years. Our products offer the attraction of guaranteed consistency in the high quality of material, method of installation and easy maintenance.

Harton, Unit 6 Thistlebrook Industrial Estate, Eynsham Drive, London SE2 9RB

Tel: 020 8310 0421 Fax: 020 8310 6785 Email: info@hartons.co.uk