

# HARTON

## vented units

### plumbing system 5

**Suitable for the flat with electric supply only.**  
**Standard Plumbing unit with direct hot water and boosted hot and cold water services.**

**This unit contains the following:**

- Sealed cold water storage tank, including ball valve and overflow connection.
- Insulated hot water cylinder two immersion heater bosses capped.
- Integrated twin 1.5 bar negative head pump boosting the hot and cold water services (larger duty pumps available).
- Interconnecting pipe work and isolation valves between the storage tank and cylinder including a cold down service.

This unit requires (by others), a 5amp spur, to the domestic booster pump, and two 3Kw power supplies to the immersion heaters, an incoming water main, overflow connection, domestic hot and cold water services connections.

As an optional extra Harton can offer fitted immersion heaters and immersion heater timer/boost controls.

**The Harton direct standard unit comes in the following sizes:**

Order code	227 ltr. cold water
22/26/120/B	610 x 1000 x 1800 high
23/26/144/B	610 x 1000 x 1800 high
24/26/166/B	610 x 1000 x 1950 high
25/26/210/B	650 x 1000 x 1800 high

*Note, the third number of the order code indicates the hot water capacity in ltrs.*

Harton can of course offer variations to the above if required, access to the unit can be front or end on.

All our potable water materials are WRAS approved.



*Harton have been designing and building Prefabricated Plumbing Units for over 50 years. Our products offer the attraction of guaranteed consistency in the high quality of material, method of installation and easy maintenance.*

Harton, Unit 6 Thistlebrook Industrial Estate, Eynsham Drive, London SE2 9RB

**Tel: 020 8310 0421 Fax: 020 8310 6785 Email: [info@hartons.co.uk](mailto:info@hartons.co.uk)**