

# HARTON

## vented units

### plumbing system 6

**Suitable for open vented heating system.**

**Standard Plumbing unit with indirect hot water cylinder, cold water storage, expansion tank and boosted hot and cold water services.**

**This unit contains the following:**

- Sealed cold water storage tank with integral heating expansion tank including ball valves and overflow connections.
- Insulated hot water cylinder with back up immersion heater.
- Integrated twin 1.5 bar negative head pump boosting the hot and cold water services (larger duty pumps available).
- Interconnecting pipe work and isolation valves between the storage tank and cylinder including a cold down service.

This unit requires (by others), a 5amp spur to the domestic booster pump, and a 3Kw power supply to the immersion heater, an incoming water main, overflow connection, domestic hot and cold water services connections.

**The Harton indirect standard units come in the following sizes.**

Order code	204/20 ltr. cold water
64/35/114/B	610 x 700 x 2050 high
65/35/140/B	610 x 700 x 2050 high
66/35/162/B	610 x 700 x 2200 high
67/35/200/B	650 x 750 x 2050 high

*Note, the third number of the order code indicates the hot water capacity in ltrs.*

Harton can of course offer variations to the above if required, access to the unit can be front or end on.

All our potable water materials are WRAS approved.



*Harton have been designing and building Prefabricated Plumbing Units for over 50 years. Our products offer the attraction of guaranteed consistency in the high quality of material, method of installation and easy maintenance.*

Harton, Unit 6 Thistlebrook Industrial Estate, Eynsham Drive, London SE2 9RB

**Tel: 020 8310 0421 Fax: 020 8310 6785 Email: [info@hartons.co.uk](mailto:info@hartons.co.uk)**