

HARTON

vented units

plumbing system 7

Suitable for sealed heating system.

Standard Plumbing unit with indirect hot water cylinder, cold water storage and boosted hot and cold water services.

This unit contains the following:

- Sealed cold water storage tank, including ball valve and overflow connection.
- Insulated hot water cylinder with back up immersion heater.
- Integrated twin 1.5 bar negative head pump boosting the hot and cold water services (larger duty pumps available).
- Interconnecting pipe work and isolation valves between the storage tank and cylinder including a cold down service.

This unit requires (by others), a 5amp spur, to the domestic booster pump, and a 3Kw power supply to the immersion heater, an incoming water main, overflow connection and domestic hot and cold water services connections.

The Harton indirect standard units come in the following sizes:

Order code	227 ltr. cold water
52/23/114/B	610 x 700 x 2050 high
53/23/140/B	610 x 700 x 2050 high
54/23/162/B	610 x 700 x 2200 high
55/23/200/B	650 x 750 x 2050 high
Order code	180 ltr. cold water
60/34/114/B	610 x 700 x 1900 high
61/34/140/B	610 x 700 x 1900 high
62/34/162/B	610 x 700 x 2050 high
63/34/200/B	650 x 750 x 1900 high

Note, the third number of the order code indicates the hot water capacity in ltrs.

Harton can of course offer variations to the above if required, access to the unit can be front or end on.

All our potable water materials are WRAS approved.



Harton have been designing and building Prefabricated Plumbing Units for over 50 years. Our products offer the attraction of guaranteed consistency in the high quality of material, method of installation and easy maintenance.

Harton, Unit 6 Thistlebrook Industrial Estate, Eynsham Drive, London SE2 9RB

Tel: 020 8310 0421 Fax: 020 8310 6785 Email: info@hartons.co.uk